HAWAII™
LED SCREEN

GM Transparent LED Screen

GM-3.9-7.8 | GM-7.8-7.8 | GM10.42 | GM 20.83



KEY FEATURES

- Ultra-light and ultra-thin, breakpoints resume
- High transparency, easy installation, simple structure
- Directly attach glass without destroying or increasing the structure

TYPICAL APPLICATION

- Sightseeing elevator
- Opening and closing doors,window glass,etc.
- Glass guardrail



HAWAII™ LED SCREEN

GM Transparent LED Screen

Model	GM-3.9-7.8	GM-7.8-7.8	GM-10.42	GM-20.83
Pixel Pitch (mm)	3.9 : 7.8mm	7.8 : 7.8mm	10.42mm	20.83mm
Pixel Configuration	1R1G1B	1R1G1B	1R1G1B	1R1G1B
Pixel Density	32768/m²	16384/m²	9216/m²	2304/m²
Module Size (WH)(mm)	1000*250mm	1000*250mm	1000*250mm	1000*250mm
Module Resolution (WH)	256*32	128*32	96*24	48*12
Transparency	75%	75%	85%	93%
Max Power Consumption	600W/m²	600W/m²	600W/m²	450W/m²
Avg Power Consumption	200W/m²	200W/m²	200W/m²	150W/m²
Brightness	5500cd/m²	4500cd/m²	4500cd/m²	3000cd/m²
Scan Method	Static Scan	Static Scan	Static Scan	Static Scan
Material	Transparent PC & Aluminum	Transparent PC & Aluminum	Transparent PC & Aluminum	Transparent PC & Aluminum
Weight	5.5kg/m²	5kg/m²	4.5kg/m²	4kg/m²
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz
Viewing Angle (H /V)	140°/140°	140°/140°	140°/140°	140°/140°
Input Voltage	AC220V/50Hz AC110V/60Hz	AC220V/50Hz AC110V/60Hz	AC220V/50Hz AC110V/60Hz	AC220V/50Hz AC110V/60Hz